






CULTIVATOR VARIO AG

- Cut-tube profile frame
- 3-point hitch on lifter
- Adjustable and movable anchors
- Welded and painted structure
- With hydraulic toothed roller (tractor oil)



MOD.	Dimensions	 Springs n°	 Tillers	Anchors height mm	Work width mm			Kg	 HP	€
AG 6	150x170x112	6	260	540	1500	150-200	1800	320	70	
AG 9	190x170x112	9	260	540	1900	150-200	2000	400	70	
AG 11	240x170x112	11	260	540	2400	150-200	2600	450	70	

CULTIVATOR VARIO AG TE80

ELECTRONIC

SQUARE SPRINGS WITH BLADE TE/80 DX



VARIO AG TE/80 EASY *Electronic*


- 550 mm blade tool
- Tractor oil operation
- Electrically operated (button) emergency retraction TE80 DX
- Hydraulic depth roller (tractor oil)
- Tractor n ° 1 pairs of double-acting hydraulic outlets

For the technical characteristics see the VARIO AG table in the previous page

AG 6 EASY

AG 9 EASY

AG 11 EASY



VARIO AG TE/80 TOP *Electronic*


- 550 mm blade tool
- Oil tank and pump
- Electrically operated (button) emergency retraction TE80 DX
- Hydraulic depth roller (tractor oil)
- Hydraulic suspended pump
- 540 rpm PTO TRACTOR
- Tractor n ° 1 pair of double-acting hydraulic outlets

For the technical characteristics see the VARIO AG table in the previous page

AG 6 TOP

AG 9 TOP

AG 11 TOP



VARIO AG TE/80 PREMIUM *Electronic*

- 550 mm blade tool
- 2 hydraulic pumps for hydraulic motorised accessories system
- Electrically operated (button) emergency retraction
- Hydraulic depth roller (button)
- OIL COOLER
- PUMP SUSPENDED FROM PTO
- PTO 540 rpm TRACTOR
- KIT HYDRAULIC ACCESSORIES

For the technical characteristics see the VARIO AG table in the previous page

AG 6 PREMIUM

AG 9 PREMIUM

AG 11 PREMIUM

